



Configuration	Size (OD)	Max Operating Torque (ft - lb)		Max Differential (kPa)		Flow rate (l/min)	Rev/Litre
		NBR-1A	NBR-HR	NBR-1A	NBR-HR		
AX962m2	244mm	10776	NA	4240	NA	2271-4542	0.057
AX800m2	203mm	12548	NA	7240	NA	1140-3400	0.058
AX800s2	203mm	9950	14930	4140	6210	1510-3410	0.042
AX650sx2	165mm	10752	NA	4230	NA	1325-2360	0.040
AX650m3	165mm	9150	13720	5900	8840	1140-2270	0.064
AX650s3	165mm	9000	13500	3620	5430	1140-2270	0.040
AX650z1	165mm	5740	NA	4960	7450	570-1550	0.087
AX650s1	165mm	8950	NA	3625	NA	760-2275	0.040
AX650m2	165mm	7950	NA	6050	NA	1140-2270	0.074
AX500mx3	121mm	4488	NA	4470	NA	570-1325	0.092
AX500s2	121mm	3500	5250	2690	4030	570-1140	0.070
AX500s3	121mm	4230	6350	3100	4650	660-1250	0.068

Size (OD)	Bit to Bend	Max WOB Dynamic	Max WOB Recommended
203mm (8")	2.55m (8.38ft)	74,000daN (166,000lbs)	43,000daN (96,600lbs)
165mm (6 1/2")	1.70m (5.58ft)	50,000daN (112,000lbs)	30,000daN (67,500lbs)
121mm (4 3/4")	1.52m (5.00ft)	36,500daN (82,000lbs)	20,000daN (45,000lbs)

www.axisenergyservices.com

Axis Energy Services Ltd. • 1100, 734 - 7th Ave SW Calgary, Alberta T2P 3P8 • 403.264.4301
 Technical Center • #6, 6125 11th Street SE Calgary, Alberta T2H 2L6 • 403.319.0444
 Service Facility • 1602 - 10th Street Nisku, Alberta T9E 0E6 • 780.955.2253